



# MGS2300R

S16R-PTA3 | 50 Hz

## MITSUBISHI DIESEL GENERATOR

\*image is for illustration purpose. It may not reflect actual product

MGS Model		MGS2300R				
Frequency (Hz)		50				
Voltage (V)		380 - 415				
Duty		Standby (ESP)	Critical Power (CP)	Prime (PRP)	Data Center Continuous Power (DCCP)	Continuous (COP)
Rated Output <sup>1</sup> (kVA)		2250		2050		1745
(kW)		1800		1640		1396
Engine Model		S16R-PTA3				
Fuel Consumption <sup>2</sup> (liter/hr) (% load)	25%	139		127		108
	50%	251		230		203
	75%	365		333		285
	100%	486		442		376
Generator	MG-	L52S7M				
Cooling System	Type	Closed looped circuit by integral radiator				
Length	(mm)	5165				
Width	(mm)	2250				
Height	(mm)	2890				
Weight (Dry)	(kg)	13600				
(Wet)	(kg)	14290				

### STANDARD & CERTIFICATIONS

- Certified to standards ISO 9001:2015
- Complies to G3 ISO8528-(1,3,5) sections, IEC60034-1 / BS EN60034-1, BS5000 Part 3, VDE00530, NEMA MG1-32, CSA22-2-100, AS1359 and UL1446
- Fully compliant with the NFPA110 Standard for Emergency and Standby Power
- Provides 100% load acceptance in one step to meet these demands

### ENVIRONMENT PARAMETER

- Relative Humidity : 85%
- Altitude above sea level: 1000m
- Ambient Temperature: 5°C - 40°C (Please consult local MGS dealer for other requirements.)

### ADVANCED CONTROL PANEL

- Rugged metal sheet with anti-vibrator isolator
- Operator-friendly interface and navigation
- Complete instrument and control accessories to meet a wide range of installation requirements
- Expansion module and custom programming are available for specific customer requirements

1: Output at 40°C, 1000m ASL with fan

2: Fuel consumption based on fuel density of 0.84 kg/L.

Fuel oil consumption may differ subject to site condition and specification of fuel. Not guaranteed value.

## COMPLETE RANGE OF ACCESSORIES

- Power Panel
- Fuel System
- Exhaust System
- Starting/Charging System
- Mechanical Driven Radiator
- Engine Protection Synchronize Module

## APPLICABLE CODES AND STANDARDS

MGS is designed in accordance with JIS, JEC, JEM, IEC, ISO (ISO15550, ISO 8528- (1,3,5) sections, ISO3046/1, JISB8002-1, DIN627, BS5514, BS5000, VDE00530, NEMA MG1-32, IEC60034, CSA (C22.2-100, AS1359) and manufacturer's standards unless otherwise specified.

Telephone Influence Factor (TIF) : Less than 50

Telephone Harmonic Factor (THF) : Less than 2%

Radio Interference : Suppression is in line with the provision of BS800 and VDE Class 0875G and 0895N

**JIS** : Japanese Industrial Standards

**IEC** : International Electrotechnical Commission

**JEC** : Japanese Electrotechnical Committee

**ISO** : International Standard Organization

**JEM** : Standards of Japan Electrical Manufacturer's Association

*\*Codes may not be available in all model configurations. Please consult local MGS dealer for availability*

## FUEL RATES

Based on ASTM D975, BS2869, and on fuel oil of 35°C API (16°C or 60°F) gravity having a LHV of 42,780kJ./kg (18,390 Btu/lb.) when used at 29°C (85°F) and weighing 838.9 g/liter (7.001lbs./U.S.gal.).

## DIESEL ENGINE

		Standby (ESP)	Critical Power (CP)	Prime (PRP)	Data Center Continuous Power (DCCP)	Continuous (COP)
Gross Engine Power (w/o fan basis)	(kWm)	1925		1750		1488
Engine Type		Four-cycled, water cooled, turbocharged with after cooler				
Speed	(RPM)	1500				
Brake mean effective pressure	(MPa)	2.4		2.1		1.8
Regenerative Absorption	(kW)	140				
No.of cylinder		16				
Broke / stroke	(mm)	170/180				
Total displacement	(liter)	65.37				
Compression ratio		14.0:1				
Piston Speed	(m/ sec)	9.0				
Noise Level at 1m (Excluding: intake, exhaust & fan)	(dB(A))	111				
Governor	Type	Digital Electrical Type				
Frequency Regulation		G3 Class				
Steady State Frequency Band		±0.25%				
Heat Rejection to coolant	(kW)	1233		1114		947
Heat Rejection to exhaust	(kW)	1624		1456		1239
Heat Rejection to atmosphere from engine	(kW)	148		134		114

## LUBRICATION SYSTEM

Lubricating Oil Capacity	L	230
Lubricating System	Type	Forced lubricating by gear pump wet sump
Lubricating Oil Filter	Type	Paper element
Lubricating Oil Cooler	Type	Water cooled corrugated

## COOLING SYSTEM

Coolant Capacity w/o Radiator /with Radiator	L	170 / 416
Coolant Pump External Resistance	kgf/cm <sup>2</sup>	0.35
Coolant Pump Flow Rate	L/min	1650
Cooling Fan Airflow Rate	m <sup>3</sup> /min	1950
Cooling Fan Airflow Restriction	kPa	0.1

## ELECTRICAL SYSTEM

System Voltage	VDC	24
Starting System		Electric Starting
Starter Motor Capacity		7.5 kW x 2
Max. Allowable Resistance of Cranking Circuit	mΩ	1.5
Recommended Minimum Battery Capacity	Ah	400 (5°C & above)
		600 (Below 5°C to - 5°C)

## GENERATOR

		Standby (ESP)	Critical Power (CP)	Prime (PRP)	Data Center Continuous Power (DCCP)	Continuous (COP)
Generator	Type	Brushless, self-excited, self-ventilated and rotating field				
Configuration		3 Phase 4 Wire				
Protection		IP23				
Power Factor		0.8 Lagging				
No of Poles		4 Poles				
Insulation Class		Class H				
Temperature Rise		Class H Peak		Class H		Class F
AVR	Type	DAVR				
Voltage Regulation	Steady State	± 0.25%				
Wave Form Distortion		5% (Non-Distorting Balanced Linear Load)				
Unbalanced Loading		Maximum 25%				
Negative Phase Sequence		Maximum 8%				
Overspeed		Maximum 125% of nominal speed				

## INLET AND EXHAUST SYSTEM

		Standby (ESP)	Critical Power (CP)	Prime (PRP)	Data Center Continuous Power (DCCP)	Continuous (COP)
Air Cleaner	Type	Paper Element				
Combustion Air Inlet Flow Rate	m <sup>3</sup> /min	169		152		130
Exhaust Flow Rate	m <sup>3</sup> /min	447		404		343
Max. Exhaust Gas Temperature	°C	550				
Exhaust Flange Size (Internal Diameter)		350A				
Allowable Exhaust Back Pressure	mm H2O	600				

## RATING DEFINITION IN ACCORDANCE WITH ISO8528-1

Duty	Overload	Load / Operating Hour		
		Avg. Load Factor/yr	Operating Hr/yr	Avg. Load Factor / 24hr
Standby (ESP)	Not Available	Maximum 70%	Maximum 500 hours	1. Maximum 80% 2. 100% in emergency
Prime (PRP)	+10% Overload	Maximum 70%	Unlimited	1. Maximum 80% 2. Overload operation (<110%) is limited to a maximum of 1hr per 12 hrs 3. Over 90% load operation limited to a maximum of 3 hrs/24hrs
Continuous (COP)	Not Available	Maximum 100%	Unlimited	Maximum 100%
Critical Power (CP) <sup>3</sup>	Not Available	Maximum 100%	Unlimited	Maximum 100%
Data Center Continuous Power (DCCP) <sup>3,4</sup>	+10% Overload	Maximum 100%	Unlimited	1. Maximum 100% 2. Overload operation (<110%) is limited to a maximum of 1hr per 12 hrs

3: UPTIME compliant: This DCCP rating meets the requirement of a Tier III and Tier IV data center site with no runtime limitation when the operation is loaded to 'N' demand for the engine generator set.

4: +10% overload is not recognized by Uptime for Tier Certification.

Mitsubishi Heavy Industries Engine System Asia Pte. Ltd. serves customers with products that are continually improved. Therefore, specifications and some materials may be changed without notice. The International System of units (SI) is used in this publication.

SC.MGS2300R.L.50.2024.Ver 1.0



### Mitsubishi Heavy Industries Engine System Asia Pte. Ltd.

3 Tuas Avenue 12, Singapore 639024

Tel: +65 6862 2202

Website: [www.mhi.com/group/mhiesa/](http://www.mhi.com/group/mhiesa/)

MOVE THE WORLD FORWARD MITSUBISHI  
HEAVY  
INDUSTRIES  
GROUP